



## 12V50H (12V) 緊急照明燈套件

### (12V) Automatic Emergency Lighting Unit

產品型號 Model No.	12V50H
外殼 Housing	金屬材料，外焗塗粉狀樹脂漆油 Metal materials with Epoxy Powder Coating
充電池 Rechargeable Battery	鉛酸密封式 12V10Ah (12 小時內充滿) Sealed Lead-Acid Rechargeable Battery 12V10Ah (full charged within 12 hours)
照明光度 Bulb	12V20W ~ 50W (2 米之外有超過 2 個燭光以上) 12V20W ~ 50W (excess 2 meters more than 2 lux)
燈內裝置 Inner Features	防火線路版及UL 防火電子線 Fire Resistant P.C.Board & UL Fire Resistant Wire
燈外裝置 Outside Features	紅色電源指示燈及測試掣 "RED" power indication light & "TEST" Switch
可亮時間 Discharge Duration	2 小時以上 Over 2 Hours
系統模式 System Mode	長明式 / 後備式 Maintained Type / Non-Maintained Type
鎮流器 Ballast	電子鎮流器 (不包括在燈內) Electronic Ballast (Not include inside)
線路設計 Circuit Design	一份低電壓斷路器，以便於充電池耗盡後將電池截斷 A low voltage cut out to disconnect the battery when fully discharged
測試標準 Testing Standard	香港消防處牌照及審批總區 [PPA/104(A) 第四次修訂] HKFSD Licensing & Certification Command [PPA/104(A) 4 <sup>th</sup> revision]
防偽裝置 Anti-Counter Feint Features	外貼鐳射標籤，內有 HI LUX QC PASS Body Anti-Counter Feint Laser Label, Inner Sticker HI LUX QC PASS
輸入電壓 Input Voltage	220V ~ 240V AC 50/60Hz
重量 Weight	6.2 千克 6.2 kg
尺寸(毫米) Dimensions (mm)	370 x 160 x 60
附加功能 Optional Function	可用於 12V MR16 LED 燈 Used in 12V MR16 LED Lamp