



## 6V3X (發光二極管) 天花式強力緊急照明燈

### (LED) High Power Ceiling Type Automatic Emergency Light

產品型號 Model No.	6V3X	
外殼 Housing	金屬材料，外焗塗粉狀樹脂漆油 Metal materials with Epoxy Powder Coating	
燈頭 Head Lamp	直徑 70 毫米，可左右轉動 Diameter 70mm rotation of left and right	
充電池 Rechargeable Battery	鉛酸密封式6V4.5Ah (12 小時內充滿) Sealed Lead-Acid Rechargeable Battery 6V4.5Ah (full charged within 12 hours)	
充電時間 Recharge Period	12 小時 12 Hours	
輸出功率 Normal Output	3W x 2 (2 米之外有超過 2 個燭光以上) 3W x 2 (excess 2 meters more than 2 lux)	
燈內裝置 Inner Features	防火線路版及UL 防火電子線 Fire Resistant P.C.Board & UL Fire Resistant Wire	
燈外裝置 Outside Features	紅色電源指示燈、綠色充電池指示燈、測試掣及有OFF掣 "RED" power indication light, "GREEN" re-charger battery light, "TEST" Switch and "OFF" button	
可亮時間 Discharge Duration	3 小時以上 Over 3 Hours	
系統模式 System Mode	後備式 Non-Maintained Type	
線路設計 Circuit Design	一份低電壓斷路器，以便於充電池耗盡後將電池截斷 A low voltage cut out to disconnect the battery when fully discharged	
測試標準 Testing Standard	香港消防處牌照及審批總區 [PPA/104(A) 第四次修訂] HKFSD Licensing & Certification Command [PPA/104(A) 4 <sup>th</sup> revision]	
防偽裝置 Anti-Counter Feint Features	外貼鐳射標籤，內有 HI LUX QC PASS Body Anti-Counter Feint Laser Label, Inner Sticker HI LUX QC PASS	
輸入電壓 Input Voltage	220V ~ 240V AC 50/60Hz	
重量 Weight	2.4 千克 2.4 kg	
尺寸(毫米) Dimensions (mm)	面蓋 : 345 x 155 x 1      底箱 : 330 x 140 x 65 Cover : 345 x 155 x 1      Bottom : 330 x 140 x 65	
附加功能 Optional Function	6V3X (明裝) : 330 x 140 x 65	