

LED - 15Y - 1




LED - 15Y - 5



LED - 15Y - 6



LED - 15Y - 7



LED - 15Y - 8



LED - 15Y - 9



LED - 15Y - 10



LED - 15Y - 11

LED-15YS, LED-15YD 水晶吊牌緊急出路燈箱 (發光二極管)

Emergency LED Exit Sign Plate

產品型號 Model No.	LED-15YS	LED-15YD
外殼 Housing	金屬材料，外焗塗粉狀樹脂漆油 Metal materials with Epoxy Powder Coating	
充電池 Rechargeable Battery	鎳鎘 / 鎳氫充電池 6V 1300mAh Ni-Cd/Ni-MH 6V 1300mAh	
充電時間 Recharge Period	12 小時 12 Hours	
輸出功率 Normal Output	≤ 3.5W	
燈內裝置 Inner Features	防火線路版及UL 防火電子線 Fire Resistant P.C.Board & UL Fire Resistant Wire	
燈外裝置 Outside Features	紅色電源指示燈及測試掣 "RED" power indication light & "TEST" Switch	
可亮時間 Discharge Duration	3 小時 3 Hours	
系統模式 System Mode	長明式 Maintained Type	
測試標準 Testing Standard	香港消防處牌照及審批總區：消防裝置及設備守則 5.10文件 HKFSD Licensing & Certification Command : Fire Service (Installations and Equipment Regulations) (Cap. 5.10)	
防偽裝置 Anti-Counter Feint Features	外貼鐳射標籤，內有 HI LUX QC PASS Body Anti-Counter Feint Laser Label, Inner Sticker HI LUX QC PASS	
輸入電壓 Input Voltage	220V ~ 240V AC 50/60Hz	
重量 Weight	鐵箱：2.4 千克 + 水晶吊牌：1.3 千克 Case Box : 2.4 kg + Plate : 1.3 kg	
尺寸(毫米) Dimensions (mm)	鐵箱：525 x 80 x 60 + 水晶吊牌：460 x 180 x 12 Case Box : 525 x 80x 60 + Plate : 460 x 180 x 12	
外形 Style	單面水晶吊牌 Single Side Plate	雙面水晶吊牌 Double Side Plate
附加功能 Optional Function	閃亮裝置功能 Flashing Device Function	