



LED-5WS 緊急出路燈箱 (發光二極管)

Emergency LED Exit Sign Box

產品型號 Model No.	LED-5WS
外殼 Housing	金屬材料，外焗塗粉狀樹脂漆油 Metal materials with Epoxy Powder Coating
充電池 Rechargeable Battery	鎳鎘/ 鎳氫充電池 6V 1300mAh Ni-Cd/Ni-MH 6V 1300mAh
充電時間 Recharge Period	12 小時 12 Hours
輸出功率 Normal Output	≤ 3.5W
燈內裝置 Inner Features	防火線路版及UL防火電子線 Fire Resistant P.C.Board & UL Fire Resistant Wire
燈外裝置 Outside Features	紅色電源指示燈及測試掣 "RED" power indication light & "TEST" Switch
可亮時間 Discharge Duration	3 小時以上 Over 3 Hours
系統模式 System Mode	長明式 Maintained Type
測試標準 Testing Standard	香港消防處牌照及審批總區：消防裝置及設備守則 5.10文件 HKFSD Licensing & Certification Command : Fire Service (Installations and Equipment Regulations) (Cap. 5.10)
防偽裝置 Anti-Counter Feint Features	外貼鐳射標籤，內有 HI LUX QC PASS Body Anti-Counter Feint Laser Label, Inner Sticker HI LUX QC PASS
輸入電壓 Input Voltage	220V ~ 240V AC 50/60Hz
重量 Weight	1.3 千克 1.3 kg
尺寸(毫米) Dimensions (mm)	195 x 195 x 60
附加功能 Optional Function	閃亮裝置功能 Flashing Device Function